KATALOR

SHANGHAI KATALOR ENTERPRISES CO., LTD.

Tel:0086-21-61182423 Website:www.katalor.com

EN10025 S275JR/J2/J0 Angel Steel

S275JR/J2/J0 Angle steel belongs to low-alloy structural steel, and S275JR/J2/J0 Angle steel is a kind of simple section steel. Besides, S275JR/J2/J0 Angle steel is mainly used for metal components framework of work shop. S275JR/J2/J0 Angle steel has excellent weld-ability, plastic deformation properties and mechanical strength.

According to the various needs about structure, S275JR/J2/J0 Angle steel can make up different stress components. S275JR/J2/J0 Angle steel is widely used in various kinds of architectural structure and engineering structure, such as beam, bridges, transmission tower, lifting transportation machinery, ship, reaction tower, container frame etc.

S275JR/J0/J2 Angel Steel Chemical Requirements:

Material	C% max			Si %	Mn %	P %	S %	N %	Cu %	Other %
	≤16	>16, <u>≤</u> 4	>40	max	max	max	max	max	max	max
S275JR	0.21	0.21	0.21	-	1.50	0.035	0.035	0.012	0.55	_
S275J0	018	0.18	0.18	-	1.50	0.030	0.030	0.012	0.55	_
S275J2	0.18	0.18	0.18	-	1.50	0.025	0.025	_	0.55	_

	Tensile strength Mpa										
Material	Normal thickness mm										
	≤3	>3,≤100	>100,≤150	>150,≤250	>250,≤400						
S275JR	430-580	410-560	400-540	380-540	_						
S275J0	430-580	410-560	400-540	380-540	_						
S275J2	430-580	410-560	400-540	380-540	380-540						

KATALOR

SHANGHAI KATALOR ENTERPRISES CO., LTD.

Tel:0086-21-61182423 Website:www.katalor.com

S275JR/J0/J2 Angel Steel Mechanical Properties:

	Minimum yield strength Mpa												
Material	Normal thickness mm												
	≤16	>16, <u>≤</u> 4	>40, <u>≤</u> 6	>63,≤80	>80,≤100	>100,≤150	>150,≤200	>200, <u><</u> 2 50					
S275JR	275	265	255	245	235	225	215	-					
S275J0	275	265	255	245	235	225	215	-					
S275J2	275	265	255	245	235	225	215	195					

		Minimum percentage elongation after fracture %											
Materi al	L0=80mm Normal thickness mm					L0=5.65 √ S0 mm Normal thickness mm							
an an	≤1	>1,≤	>1.5,≤	>2,≤2.	>2.5,	≥3,	>40 <u>,≤</u> 6	>63,≤10	>100,≤15	>150,≤25	>250, <u>≤</u> 40		
		0.5	2	5	<3	≤40	3	0	0	0	0		
S275J R	15	16	17	18	19	23	22	21					
S275J0	14	15	16	17	18	22	21	20	19	18			
S275J2	13	14	15	16	17	21	20	19			17 (I and t)		

Material	Minimum energy (J) Normal thickness mm									
Waterial	Temperature	≤150	>150,≤250	>250,≤400						
S275JR	20	27	27	_						
S275J0	0	27	27	_						
S275J2	-20	27	27	27						



SHANGHAI KATALOR ENTERPRISES CO., LTD.

Tel:0086-21-61182423 Website:www.katalor.com

Shanghai Katalor was established more than ten years ago with valuable experience in steel marker, Shanghai Katalor has ability to deal with problems you raised. Besides, we can design the products according to the drawing you provided. What's more, with high precision, strictly inspection and excellent performance, we not only have ability to offer S275JR/J2/J0 Angel Steel products, but also can provide supreme after-sale service about S275JR/J2/J0 Angel Steel. We sincerely hope to be your reliable supplier of S275JR/J2/J0 Angel Steel.